

SRS Mihagran FO 2320/3 KOR



Mould Release Oil

October 2011

Characteristics

Mould release oils can vary in their composition greatly. Various requirements in practice demand different levels of viscosity. The addition of active ingredients can vary also with regard to chemistry and concentration.

Mihagran FO 2320 / 3 KOR is a low viscous mould release oil with additives to improve the release effect and corrosion protection. It is suitable for use in steel and plastic moulds with smooth surfaces. The product can be applied with a brush, manually or by spraying in a very thin release oil film.

SRS Mihagran FO 2320 / 3 KOR is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Mihagran FO 2320 / 3 KOR
Designation		DIN 51 502	FS
Colour		DIN ISO 2049	L 1.0
Density at 15°C	g/cm ³	DIN 51 757	0.870
Kin. Viscosity at 20°C	mm ² /s	DIN EN ISO 3104	18.5
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	8.6
Flash Point COC		DIN ISO 2592	150
Pour Point		DIN ISO 3016	-15
Neutralization Number		DIN 51 558	8.9
Ash (oxide)		DIN EN 6245	0.03
Steel Corrosion		DIN 51 585	0-A

The above values may vary within the commercial limits.

Made in Germany